

Pro-Seal Aqua Flex™

Liquid Applied Elastomeric Coating



Pro-Seal Aqua Flex™ is a single component elastomeric coating with exceptional elongation and elasticity. * Polycarbon/polycarbonate integrated technology

- Easy to install
- Use on substrates that require expansion & contraction over broad temperature ranges (-20°F to 180°F)
- Easy to repair
- May bridge minor surface imperfections
- Custom colors available

Applications: Concrete, CMU Block, Stucco and areas of greater expansion and contraction requiring a water barrier

Technical

| Information | Value |
|--------------------------------|--|
| Material | 1 part |
| Appearance | Liquid |
| Application temp. | > 53°F |
| Application humidity | < 80% |
| Stain resistance | Good |
| Dry film | 6-8 mils |
| Density | 8.2-8.5 lbs/gal |
| Color | White |
| Spread rate: 10 mils 7 mils | 100 ft ² . / gal 150 ft ² . / gal |
| Solids | 62.5% weight x 49% volume |
| Tack free cure time | 2-4 hours |
| Dry cure time | 8 hours |
| Shelf life | 24 months when stored properly |
| Storage indoors | 60°F-110°F |
| Packaging: | 1, 5 and 55 gallons |

Application Instructions: Surface must be dry, clean and free of all loose particulate and bond-breaking matter. For specific application instructions or guide specifications, contact us at 800.349.7325 or information@prosealproducts.com

Specifications

| ASTM/Test | Data | Value |
|-----------------------|------------------------------|---|
| D 2370 | Tensile strength @ 75°F | 655 psi |
| D 2730 | Elongation @ 75°F | 350% |
| D 1653 | Water vapor permeance @ 75°F | 9 perm |
| D 822 | Weathero-meter | No deterioration or chalking after 2,000 cycles |
| Brookfield viscometer | Viscosity | 110-116 ku |
| D 2369-2398 | V.O.C. content | 50 g/l |

* Data based on laboratory tested materials.

Technical Support: Contact our technical department 800.349.7325, information@prosealproducts.com or visit our website www.prosealproducts.com for additional information

Cautions: Keep out of reach of children. May cause skin or eye irritation. This product may be harmful if swallowed. Do not induce vomiting. Contact a physician immediately and always seek a physician's advice regarding first aid. Use only in commercial or industrial applications. Use only on intended surfaces. Contact manufacturer for specific application uses. See material safety data sheet for additional cautions.

Limited Warranty: We warrant our product to be free of defects in material and workmanship; and to be in accordance with our company quality control standards. All data, statements, and recommendations, made herein are based upon information we believe to be reliable, but are made without any representation, guarantee, or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for the user's own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations. Liability under any condition shall be limited to replacement of material only.