

# Pro-Seal DP-36<sup>®</sup>



## Fluid Contaminant Extractant & Deep Penetrating Sealer

### Product Description

Pro-Seal DP-36<sup>®</sup> is a single component polycarbon/polycarbonate reactive osmotic reagent that seals, densifies, hardens, reduces vapor drive and preserves most concrete substrates when used as part of a Pro-Seal<sup>®</sup> system.

### Advantages

- No V.O.C.
- Leaves a clear natural finish with no film or membrane on the surface
- Provides a prepared surface for better bonding of concrete toppings, coatings, mastics, and paints
- Extracts fluid contaminants from the in situ structures of concrete
- Forms a hydrostatic barrier in concrete that greatly reduces vapor drive
- Gives concrete some waterproof characteristics.

### Applications

- On Grade
- Below Grade
- Negative Side
- Vertical or Horizontal applications

\*Intended for use on concrete only. Not intended for pigmented surfaces. Keep away from glass. Always apply a test patch before application. Pro-Seal DP-36<sup>®</sup> will not bridge cracks, voids or gaps. Use only on intended surfaces, protection of property required.

### Technical Support

For technical support: 425.488.6570 or [information@prosealproducts.com](mailto:information@prosealproducts.com)

### Instructions

1. Surface must be clean and free of all loose particulate and bond-breaking matter.
2. Wet area with de-ionized water, leaving no standing water.
3. Apply at an average coverage rate of between 600 and 800 square feet per gallon using a low-pressure sprayer.
4. Wait for 48 hours, then apply the Pro-Seal<sup>®</sup> specified system.
5. For specific application instructions or guide specifications, contact Pro-Seal's Technical Department at 425.482.1671

### Technical

Information	Value
Material	1 Part
Mix Time	N/A
Appearance	Liquid
Application	See Guide Specification
Cure Time	48 Hrs Walk able
Full Cure	14 Days
Freezing Temp	32°F
Boiling Point	212°F
Flammability	None
Environmental Hazards	None
Shelf Life	2 Years When Stored Properly
Packaging	1 Gallon 5 Gallons 55 Gallons

Pro-Seal DP-36<sup>®</sup>



16541 Redmond Way • Suite 363C • Redmond, WA 98052  
Phone: 425.482.1671 • Fax: 425.488.6926 • [information@prosealproducts.com](mailto:information@prosealproducts.com)  
[www.prosealproducts.com](http://www.prosealproducts.com) • © Copyright Pro -Seal