

PRODUCTS, INC.

The Pro-Seal Anti-Graf System™ is environmentally friendly system that literally melts "graffiti" away before your eyes!



Features:

- Non-sacrificial sealing and graffiti removal system
- Weatherproofs
- May be tinted upon request
- Phosphate free
- UV impervious, non-yellowing
- Clear invisible non-sheen seal
- Zero V.O.C.
- Single component



Apply to concrete, rough concrete, decorative concrete, tile, metal, CMU, stone, masonry, brick, bathroom stalls and other appropriate substrates.

Advantages



- Long lasting and durable
- Graffiti is easily removed
- Cost effective and labor saving
- Environmentally friendly
- Will not alter color or texture or substrate
- Spot repairable
- Easy to apply
- Easy to maintain

PRO-SEAL[®]

PRODUCTS, INC.

Perfect non-toxic product to remove distracting unprofessional graffiti "tags" from street signs, schools, hospitals, warehouses, parks and more!



Graffiti Sealant Application Instruction (Anti-Graf)

1. The surface must be clean, dry and free of all bond breaking matter; such as but not limited to dirt, dust, minerals, salt, paint, sealer and coatings.
2. Apply the first coat of Pro-Seal Anti-Graf to concrete, masonry, metal, brick, or other appropriate surfaces at a coverage rate of 350 ft² per gallon in a horizontal pass.
Note: Coverage rate may vary based on density and porosity of the substrate.
3. Allow Pro-Seal Anti-Graf to dry to the touch.
4. Repeat step 2 applying product in a vertical pass.
5. Allow Pro-Seal Anti-Graf to dry to the touch.



Graffiti Removal Instruction (De-Graf)

1. Spray Pro-Seal De-Graf (do not dilute) onto the tagged surface that has been pre-treated with Pro-Seal Anti-Graf. If applied to a surface not pre-treated with Anti-Graf, you may need to alter application.
2. Use a stiff brush in a circular motion to loosen the graffiti. Note: Do not use a wire brush, it may damage the Anti-Graf. If you damage the Anti-Graf; once clean, a simple spray-on application will spot repair the seal.
3. Rinse the surface with a nozzled hose or power rinse at 800# or less. Repeat steps 1-2 until clean.

16541 Redmond Way • Suite 363C • Redmond, WA 98052

800.349.7325 • www.prosealproducts.com • information@prosealproducts.com