

Pro-Seal Hydro Paint Rubberized™



Polycarbon/Polycarbonate Rubberized Coating

Hydro Paint Rubberized™ is a single component, synthetic rubber elastic coating. This product has been designed for use as a mild range chemical resistant coating. **Polycarbon/polycarbonate integrated technology.*

- Easy to install
- High density
- 50% solid
- May be applied in damp environments when used with Pro-Seal DP-36®
- Has a wide range of good chemical resistance
- Unlike epoxies and urethanes as it is easily spot-repairable

Applications on concrete: Harsh environments, Water tanks, Holding tanks, Ponds, Pools and Mild secondary containment

Technical

Information	Value
Material	1 Part
Appearance	Liquid
Flash Point	500°F
Coverage Rate	100-400 ft ² /gallon*
Stain Resistance	Excellent
Cure To Touch	1 Hour
Cure To Recoat	24 Hours
Full Cure	48 Hours
Shelf Life	Up to 12 months when stored properly
Packaging:	1, 5 or 55 gallons

*Depending on substrate

Specifications

Test	Data	Value
ASTM D 695	Compressive Strength	1,000 psi
ASTM D 1706	Cured Hardness	85 shore D
ASTM D 638	Tensile Strength	900 psi
ASTM D 2566	Cure Shrinkage	.003 Inches
ASTM D 790	Flexural Strength	900 psi
ASTM D 1002	Adhesive Tensile Shear	400 psi
Taber Abrasion Resistance	1,000 gm head cs 17 wheel weight loss 1,000 Cycles	1 mg
Taber Abrasion Resistance	1,000 gm head cs 17 wheel weight loss 350,000 Cycles	Removed

* Data based on laboratory tested materials.

Application Instructions: Surface must be dry, clean and free of all loose particulate and bond-breaking matter. For specific application instructions or guide specifications, contact Pro-Seal's Technical Department at 800.349.7325 or information@prosealproducts.com

Chemical Resistance

Cured Material	Rating
Hydrochloric Acid	Excellent
Sulfuric Acid 60%	Fair
Nitric Acid 25%	Poor
Chromic Acid	Fair
Kerosene	Fair
Methanol	Very Good
Toluene	Poor
Ammonia	Good
Nitrates	Fair
Phenol	Poor
Sodium Hydroxide 10%	Good
Chlorinated Solvent	Good

Technical Support: Contact our technical department at 800.349.7325, information@prosealproducts.com or visit our website www.prosealproducts.com for additional information.

Cautions: Keep out of reach of children. May cause skin or eye irritation. This product may be harmful if swallowed. Do not induce vomiting. Use in well ventilated area. Contact a physician immediately and always seek a physician's advice regarding first aid. Use only in commercial or industrial applications. Use only on intended surfaces. Contact manufacturer for specific application uses. See material safety data sheet for additional cautions.

Limited Warranty: We warrant our product to be free of defects in material and workmanship; and to be in accordance with our company quality control standards. All data, statements, and recommendations, made herein are based upon information we believe to be reliable, but are made without any representation, guarantee, or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for the user's own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations. Liability under any condition shall be limited to replacement of material only.

