

Pro-Seal Pro-Cure A™

Type 1, Class A & B Curing Compound



Pro-Cure A™ is a single component, non-solvent, film-forming concrete curing agent. This product has been designed to dissipate when exposed to solar light or heat and cure new concrete to its maximum strength.

**Polycarbon/polycarbonate integrated technology.*

- Easy to install
- Non-solvent
- Creates a moisture resistant film membrane
- Meets or exceeds V.O.C. compliance for California State Regulation, Organic Compounds Rule 3

Applications: Use for curing new concrete

Application Instructions: Surface must be clean and free of all loose particulate and bond-breaking matter. For specific application instructions or guide specs, contact Pro-Seal's Technical Department at 800.349.7325 or information@prosealproducts.com

Technical

Information	Value
Material	1 part
Appearance	Liquid
Volatile organic content	73.548 gram/liter
Penetrates	1-22 mils
Flash point	230°F
Cure time to walk	45 minutes
Full cure	1.5 hours
Specific gravity	8.46
Coverage rate	200-250 ft ² /gallon
Packaging:	1, 5 or 55 gallons

Technical Support: Contact our technical department at 800.349.7325, information@prosealproducts.com or visit our website www.prosealproducts.com for additional information.

Specifications

Test	Data	Value
Brookfield viscometer	Viscosity @ 75°F	20 cps
ASTM D 471	Water absorption Low air content	.10% weight
ASTM D 471	Water absorption normal air content	.18% weight
ASTM C 672	Freeze/thaw damage @ ambient	No damage
ASTM C 672	Freeze/thaw damage chloride content	7%
ASTM C 672	Freeze/thaw damage non air-entrained	1.5% @ 2.45cm
ASTM C 672	Freeze/thaw damage air entrained	7% @ 2.45cm

** Data based on laboratory tested materials.*

Cautions: Keep out of reach of children. May cause skin or eye irritation. This product may be harmful if swallowed. Do not induce vomiting. Use in well ventilated areas. Contact a physician immediately and always seek a physician's advice regarding first aid. Use only in commercial or industrial applications. Use only on intended surfaces. Contact manufacturer for specific application uses. See material safety data sheet for additional cautions.

Limited Warranty: We warrant our product to be free of defects in material and workmanship; and to be in accordance with our company quality control standards. All data, statements, and recommendations, made herein are based upon information we believe to be reliable, but are made without any representation, guarantee, or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for the user's own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations. Liability under any condition shall be limited to replacement of material only.