

Pro-Seal Ultra Shield II-A™

Decorative Concrete Sealer



Ultra Shield II-A™ is a hydrocarbon resistant film sealer for decorative concrete. This product is available in custom colors. *Polycarbon/polycarbonate integrated technology.

- Spot repairable
- Easy to apply
- Excellent stain resistances
- May be applied over other sealers
- Prevents moisture penetration
- Prevents freeze-thaw damage, spalling, chipping, and crumbling of brick & concrete
- Enhances the appearance of many surfaces while remaining ultra clear
- Penetrates up to 1/8" into the substrate

Technical

Information	Value
Material	1 part
Mix time	N/A
Appearance	Liquid
Cure time to touch	1 hour
Full cure	96 hours
Second coat needed within	2 hours
Flammability	Non flammable
Coverage rate	350-900 ft ² /gallon
Weight per gallon	8.44 lbs
Packaging:	1, 5 and 55 gallons

Chemical Resistance

Cured material	Rating
Aliphatic hydrocarbons	10
Aromatic hydrocarbons	10
Black & print	10
Water	10
Oil	10
Wine	10
Citrus	10
Gasoline	10
Adhesion to substrate	10
Atmospheric contaminants	10
Slip & skid	10
Black tire mark	10
Key: 0 = complete failure; 10 = excellent	

Applications on Concrete: Countertops, Sinks, Floors, Patios, Fireplaces, Bars, Islands, etc...

Application: Surface must be dry, clean and free of all loose particulate and bond-breaking matter. For specific application instructions contact Pro-Seal's Technical Department at 800.349.7325 or information@prosealproducts.com

Technical Support: Contact our technical department at 800.349.7325, information@prosealproducts.com or visit our website www.prosealproducts.com for additional information

Cautions: Keep out of reach of children. May cause skin or eye irritation. This product may be harmful if swallowed. Do not induce vomiting. Use in well ventilated areas. Contact a physician immediately and always seek a physician's advice regarding first aid. Use only in commercial or industrial applications. Use only on intended surfaces. Contact manufacturer for specific application uses. See material safety data sheet for additional cautions.

Limited Warranty: We warrant our product to be free of defects in material and workmanship; and to be in accordance with our company quality control standards. All data, statements, and recommendations, made herein are based upon information we believe to be reliable, but are made without any representation, guarantee, or warranty of accuracy. Our products are sold on the condition that the user himself will evaluate them, as well as our recommendations, to determine their suitability for the user's own purpose before adoption. Also, statements regarding the use of our products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations. Liability under any condition shall be limited to replacement of material only.