

MATERIAL SAFETY DATA SHEET

WHMIS Hazard Classification: H F R P

Date: 9.1.08

SECTION I PRODUCT IDENTIFICATION

Product Identifier: Pro-Seal Weathermaster
Product Use: Top Coat Sealer
Supplier's Name: Pro-Seal Products
Address: 16541 Redmond Way Suite 363C
Redmond, WA 98052
Emergency Number: (800) 424-9300

Information: (800) 349-7325

SECTION II HAZARDOUS INGREDIENT

Table with 5 columns: Compound, %, CAS#, LD50 Species/Route, LC50 Species/Route. Row 1: Mineral Spirits, 500/PEL ppm.

SECTION III PHYSICAL DATA

Odor & Appearance: Colorless with Aliphatic odor
Physical State: N/A
Specific Gravity: H2O-1 Barrier Type B
Vapor Density: Air-1 Heavier
Boiling Point: 340- 415
pH: N/A
Odor Threshold: N/A
Evaporation Rate: (Butil-1) Slower
Vapor Pressure: mm Hg @ 68°F Less 2mm
Freezing Point: N/A
Solubility in Water: Negligible

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method): 106°F T.C.C.
Auto Ignition Temp:
Extinguishing Media: Foam CO2, dry chemical
Special Fire Fighting Procedures: Wear MESA/NOISH approved self-contained breathing apparatus.
Unusual Fire and Explosion Hazards: Products of combustion are toxic.
Sensitivity to Static Discharge: N/A
Sensitivity to Impact: N/A

SECTION V REACTIVITY DATA

Stability: Yes
Incompatibility: Strong oxidizers
Hazardous Decomposition Products: Thermal
Hazardous Polymerization: N/A

SECTION VI TOXICOLOGICAL DATA

Route of Entry: Inhalation, Ingestion

Exposure Limits:

Effects of Acute Exposure: headache, nausea, nose, skin throat and lung irritation, EG may cause drowsiness, nausea and slurred speech.

Effects of Chronic Exposure: EG may cause dizziness, stupor, unconsciousness. Harmful if swallowed, can cause kidney damage, fatal in large doses.

Carcinogenicity, Reproductive Toxicity, Teratogenicity, Mutagenicity: Not listed as carcinogen.

Toxicologically Synergistic Products:

SECTION VII PREVENTATIVE MEASURES

Respiratory Protection: None if standard draft or ventilation is maintained. Do not breathe in over spray. Vapor mask should be used if there is no draft or ventilation.

Ventilation: Breeze or standard ventilation

Protective Gloves: Yes

Eye Protection: Yes, safety equipment should be worn on all application/construction (ANZI 2-8) sites.

Other Protective Equipment: Safety boots, pants, etc. (respirators should be MSHA/NOISH approved pressure demand)

Leak or Spill Procedures: Keep spectator from area. Dike and contain with inert material. Keep out of sewers. Re-contain and use or dispose if not usable.

Waste Disposal: Dispose of material solidifies with lime and ferric chloride and incinerate. Flush supernatant liquids to chemical sewer.

Precautions to be taken in Handling and Storage: Keep temps in greater than 1°C/34°F less than 49°C/120°F ranges.

Storage Requirements: Keep away from children.

SECTION VIII CONTROL MEASURES/PROTECTION INFORMATION

Emergency and First Aid Procedures:

Wash skin with soap and water if contact occurs.

Eye was facility/ safety showers recommended if acute or chronic exposure occurs for 15 minutes.

Inhalation: Move subject to fresh air. Artificial respiration if breathing stops.

Ingestion: Dilute by drinking water, do not induce vomiting, call a physician

SECTION IX PREPARATION INFORMATION

Judgments as to the suitability of information herein for purchaser's purposes are necessarily purchaser's responsibility. Therefore, although reasonable care has been taken in the preparation of such information. Pro-Seal Systems Div ICP, Inc extends no warranties, makes no representations and assumes no responsibility as to the accuracy or suitability of such information for application to purchaser's intended purposes of for consequences of its use.

Created By: MF